## **BRIDGESTONE SPECIFICATION CODES**

Each Bridgestone off road tire has its own specification code that enables the customer to properly identify and match the right Bridgestone tire which will best meet the conditions under which the tire will be used.

SERVICE  E: Earthmover  D: Loader & Dozer  G: Grader		1A: Standard 2A: Cut Resistant 3A: Heat Resistant					
				EXAMPLE	E3A = Earthmover and Heat Resistant		
				NOTE	DE2 = Combined D2A and E2A		
				ADDITIONAL COMPOUND CONSTRUCTION COMMENTS	IDU = Industrial LS = Special Cut Resistance N/A = Not Applicable LAC = Load and Carry DAL = Dig and Load NY = Nylon NS = Nylon Steel		

METRIC SIZE CONVERSION CHART				
METRIC SIZE	EQUIVALENT SIZE	OPTIONAL SIZE		
385/95R24	14.00R24			
385/95R25	14.00R25			
445/80R25	17.5R25			
445/95R25	16.00R25			
525/80R25	20.5R25			
550/65R25		20.5R25		
600/65R25		23.5R25		
650/65R25		23.5R25		
750/65R25	30/65R25			
775/65R29		26.5R25		

29.5R25

## **CONVERSION CHART** [STAR RATING TO PLY RATING]

875/65R29

SERVICE	TIRE SIZE	STAR RATING	CORRESPONDING PLY RATING
GRADER	14.00R24	*	up to 16
	16.00R24	*	up to 16
	17.5R25	*	up to 16
EARTHMOVER	12.00R24	***	up to 24
	14.00R24	***	up to 32
	14.00R25	***	up to 32
	16.00R25	**	up to 36
	18.00R25	*	up to 24
		**	up to 36
	18.00R33	**	up to 40
	21.00R33	**	up to 36
	21.00R35	**	up to 44
	24.00R35	**	up to 48
	24.00R49	**	up to 48
	27.00R49	**	up to 54
	30.00R51	**	up to 58
	33.00R51	**	up to 64
	36.00R51	**	up to 66
	40.00R57	**	up to 74
	17.5R25	*	up to 16
	20.5R25	*	up to 24
		**	up to 28
	25/65R25	**	up to 32
	23.5R25	*	up to 24
		**	up to 32
	26.5R25	**	up to 32
	29.5R25	**	up to 34
	29.5R29	**	up to 40
	33.25R29	**	up to 44
	33.5R33	**	up to 44
	37.5R33	**	up to 48
	33.25R35	**	up to 44
	37.25R35	**	up to 48
	37.5R39	**	up to 52
	40.5/75R39	**	up to 54
	15.5R25	*	up to 16
	17.5R25	*	up to 16
	20.5R25	*	up to 24
	20.31(23	**	up to 28
	23.5R25	*	up to 24
LOADER	23.31(23	**	up to 32
	26.5R25	*	up to 32
	20.3823	**	up to 36
	29.5R25	*	up to 28
	25.5825	**	up to 34
	29.5R29	*	up to 34
	29.5K29 35/65R33	*	up to 36
	35/65R33	**	up to 36 up to 42
		*	
	45/65R45	**	up to 50
	45/65R45	**	up to 58